
-

Tekniset tiedot:

Active/passive	: passive
Transmission method	: Cables
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 500 W
Power rating (RMS)	: 250 W
Impedance	: 8 Ohm
Frequency range	: 55-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 12/2 full range
Full range speaker	: -
Bass speaker	: 30 cm (12") bass speaker
Midrange speaker	: -
Tweeter	: 25 mm (1", 34 mm voice coil) horn tweeter
Number of speakers	: 2
Speaker size	: 30 cm (12")
Sensitivity	: 98 dB/W/m
Max. rated SPL	: 122 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: black
Mounting device	: M8 threaded inserts, stand sleeve
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 430 x 580 x 310 mm
Width	: 430 mm
Height	: 580 mm
Depth	: 310 mm
Weight	: 14.62 kg

Inputs	: 1 x SPEAKER
Outputs	: 1 x SPEAKER, par. out
Replacement voice coil	: PAB-115/VC (version 06/2015 or higher), PAB-128/VC
Other features	: -
Accessories	: PAB-112BAG