

---

-

## Tekniset tiedot:

Active/passive	: active
Transmission method	: Cables
Total output power	: 500 W
Power rating (RMS)	: DSP-controlled, 370 W (300+70) bass: 300 W tweeter: 70 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 60-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: 775 mV/20 kOhm (line, bal.), 10 mV/20 kOhm (mic, bal.)
System	: 8/2 full range bass-reflex
Full range speaker	: -
Bass speaker	: 20 cm (8") coaxial speaker
Midrange speaker	: -
Tweeter	: 25 mm (1", 44 mm voice coil) horn tweeter
Number of speakers	: 2
Speaker size	: 20 cm (8")
Sensitivity	: 97 dB/W/m
Max. rated SPL	: 118 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: multiplex
Colour	: black
Mounting device	: M10 threaded inserts (bracket mounting), M8 threaded insert (mounting safeguard), stand sleeve
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: &acd; 230 V/50 Hz/350 VA
Dimensions	: 340 x 303 x 379 mm
Width	: 340 mm
Height	: 303 mm
Depth	: 379 mm
Weight	: 10.75 kg

---

Inputs	: 2 x comb. XLR/6.3 mm (line/mic A, line B)
Outputs	: 2 x XLR, par. out, 1 x XLR MIX out
Replacement voice coil	: -
Other features	: DSP-controlled limiter
Accessories	: -