

PSS-1205DC - Switch. Power Supply 12V/500mA



Switch-mode power supply, DC 12 V/0.5 A,
high energy efficiency, corresponds to the EU ecodesign directive.

- Saves electricity costs due to low power consumption in standby mode (< 0.3 W)
- Compact lightweight design
- Protected against short circuit, overload and overheating
- Power LED
- 1.8 m connection cable
- Low-voltage plug 5.5/2.1 mm, positive pole at the internal contact

Tekniset tiedot:

| | |
|-----------------------------|-----------------------------------|
| Category | : switch-mode power supply |
| Input voltage | : ∿ 100-240 V/50-60 Hz/130 mA |
| Output voltage | : DC 12 V |
| Charging/output current | : 500 mA |
| Charging time | : - |
| Trickle charge | : - |
| Polarity selection | : - |
| Switchable output voltage | : - |
| Reactivation | : - |
| Connections | : - |
| Cable length | : - |
| Short-circuit protection | : yes |
| Overload protection | : yes |
| Overheat protection | : yes |
| Reverse polarity protection | : - |
| Detection of faulty battery | : - |
| Protective class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : 38 x 49 x 67Å mm |
| Weight | : 65 g |
| Position | : A |
| Other features | : - |