

## BR-50 - Bass Rocker

100  
W<sub>MAX</sub>

4Ω



Bass rocker, 50 W, 4 Ohm

- Special technology for producing a structure-borne sound
- Mounting to a seat or also to a floor or dance floor capable of vibrating
- Generates a powerful bass which can physically be felt
- Easy screw mounting
- Connection to suitable power amplifier via basic passive crossover network as for subwoofers, or even better via an individual amplifier
- Series or parallel connection of several BR-50 devices is possible like with common bass speakers
- Resonant frequency: 40 Hz (varies due to mounting to different surfaces)



- Frequency range: approx. 30-300 Hz
- Even mounting surface required of at least 110 x 110 mm
- Dimensions: 131 x 131 x 56 mm
- Weight: 1.232 kg

## Tekniset tiedot:

Impedance (Z)	: 4 Ohm
Transmission method	: -
Frequency range	: 30-300 Hz
Resonant frequency (fs)	: 40 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 50 W
Peak music power output (MAX)	: 100 W
Sensitivity	: no data
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X <sub>MAX</sub> )	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: not applicable
Mounting depth	: -
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: 131 x 131 x 56 mm
Outside diameter	: ~ 152 mm
Width	: 131 mm



Height	: 131 mm
Depth	: 56 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 1.232 kg
Packing unit	: 1
Type of speaker	: -