



SP-8/150PRO - PA Woofer



Compact PA bass speaker, subwoofer, 150 W, 8 Ohm

- 20 cm (8") bass speaker and subwoofer of high power capability
- Heat-resistant voice coil and ventilated drive system
- Extra long excursion for a deep bass reproduction of high volumes
- Progressive cone suspension for a high operating reliability
- Robust diecast aluminium basket
- Ideally suited for 2-way systems and compact subwoofers



“An excellent bass-midrange speaker with an impressive level stability for 2-way and 3-way applications. It features an excellent price-performance ratio.”

Tekniset tiedot:

| | |
|---|----------------------------------|
| Impedance (Z) | : 8 Ohm |
| Transmission method | : - |
| Frequency range | : f3-3,000 Hz |
| Resonant frequency (fs) | : 56 Hz |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : - |
| Power rating (RMS) | : 150 W |
| Peak music power output (MAX) | : 300 W |
| Sensitivity | : 93 dB/W/m |
| Max. rated SPL | : - |
| Max. voltage | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Suspension compl. (Cms) | : 0.35 mm/N |
| Moving mass (Mms) | : 22.8 g |
| Mech. Q factor (Qms) | : 1.52 |
| Electr. Q factor (Qes) | : 0.41 |
| Total Q factor (Qts) | : 0.32 |
| Equivalent volume (Vas) | : 22 l |
| DC resistance (Re) | : 7.2 Ohm |
| Force factor (BxL) | : 11.96 Tm |
| Voice coil induct. (Le) | : 2.0 mH |
| Voice coil diameter | : $\tilde{\sim}$ 50 mm |
| Voice coil former | : aluminium |
| Linear excursion (X _{MAX}) | : \pm 6 mm |
| Eff. cone area (Sd) | : 213 cm ² |
| Magnet weight | : 850 g |
| Magnet diameter | : $\tilde{\sim}$ 120 mm |
| Mounting cutout | : $\tilde{\sim}$ 185 mm |
| Mounting depth | : 90 mm |
| Mounting hole diameter | : - |
| Hole spacing X-axis | : - |
| Hole spacing Y-axis | : - |
| Dimensions | : $\tilde{\sim}$ 210 mm x 100 mm |
| Outside diameter | : $\tilde{\sim}$ 210 mm |
| Width | : $\tilde{\sim}$ 210 mm |



| | |
|-----------------------|-----------|
| Height | : - |
| Depth | : 100 mm |
| Protective class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Weight | : 2.52 kg |
| Packing unit | : 1 |
| Type of speaker | : 8" |