
-

Tekniset tiedot:

No. of channels	: 12
No. of inputs	: 27
Mic input	: 0.5 mV, bal., 12 x 3-pole XLR
Line input	: 8 mV, bal. (stereo), 2 x 6.3 mm jack L/R 2 mV, bal. (mono), 12 x 6.3 mm jack
CD input	: -
Phono input	: -
Tape (play)	: 60 mV, 1 x RCA L/R
Aux input	: 60 mV, bal., 2 x 6.3 mm jack L/R
Insert input	: 80 mV, 12 x 6.3 mm jack
Effect return	: -
Master output	: 1.5 V, bal., 1 x 3-pole XLR L/R
Record output	: -
Monitor output	: -
Booth output	: -
Aux output	: 10 V, 4 x 6.3 mm jack
Insert output	: -
Effect send	: -
Control room	: 10 V, stereo, 1 x 6.3 mm jack
Tape (rec)	: 680 mV, 1 x RCA L/R
Headphones	: ? 8Ω Ohm, 1 x 6.3 mm jack
Gooseneck lamp	: -
WiFi	: -
USB	: -
Bluetooth	: -
Frequency range	: 20-20,000 Hz
THD	: < 0.04%
S/N ratio	: 89 dB
Crosstalk	: -63 dB
Equalizer bass	: ±15 dB/80 Hz
Equalizer midrange	: ±15 dB/100-8,000 Hz (mono channels) ±15 dB/500 Hz (stereo channels) ±15 dB/3 kHz (stereo channels)
Equalizer treble	: ±15 dB/12 kHz
equalizer	: ±15 dB, 63/160/400 Hz 1/2.5/6.3/16 kHz
Talkover	: -
Phantom power	: +48 V
Crossfader	: -

Media player	: -
Amplifier	: 2 x 475 W/4 Ohm 2 x 260 W/8 Ohm 1 x 900 W/8 Ohm
Power supply	: ∿ 230 V/50 Hz/1,250 VA
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 1,250 VA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 545 mm
Height	: 145 mm
Depth	: 465 mm
Rack spaces, RS	: -
Weight	: 10.5 kg