

## IT-130 - Horn Speaker



Weatherproof horn speaker

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Power selector switch
- For open-air events, industrial use, in workshops

## Tekniset tiedot:

|                                |                         |
|--------------------------------|-------------------------|
| Active/passive                 | : passive               |
| Transmission method            | : 100 V                 |
| Total output power             | : -                     |
| Power rating (RMS)             | : -                     |
| Total power rating             | : 30 W                  |
| Power rating (RMS)             | : 30/15/10/5/3/1Â W     |
| Impedance                      | : -                     |
| Frequency range                | : 250-16,000 Hz         |
| THD                            | : -                     |
| S/N ratio                      | : -                     |
| Input signal                   | : -                     |
| System                         | : -                     |
| Full range speaker             | : -                     |
| Bass speaker                   | : -                     |
| Midrange speaker               | : -                     |
| Tweeter                        | : -                     |
| Number of speakers             | : 1                     |
| Speaker size                   | : -                     |
| Sensitivity                    | : 109 dB/W/m            |
| Max. rated SPL                 | : -                     |
| Radiation angle, horizontal    | : -                     |
| Radiation angle, vertical      | : -                     |
| Features                       | : power selector switch |
| Housing material               | : ABS                   |
| Colour                         | : white                 |
| Mounting device                | : mounting bracket      |
| Protected against ball rebound | : -                     |
| Protection class               | : IP66                  |
| Admiss. ambient temp.          | : -20 °C to +50 °C      |
| Power supply                   | : -                     |
| Dimensions                     | : 290 x 215 x 260Â mm   |
| Width                          | : 290 mm                |
| Height                         | : 215 mm                |
| Depth                          | : 260 mm                |
| Weight                         | : 1.6 kg                |



|                        |                |
|------------------------|----------------|
| Inputs                 | : -            |
| Outputs                | : -            |
| Replacement voice coil | : -            |
| Other features         | : weatherproof |
| Accessories            | : -            |