

---

-

## Tekniset tiedot:

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: f3-4,000 Hz
Resonant frequency (fs)	: 53 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 50 W
Peak music power output (MAX)	: 100 W
Sensitivity	: 88 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: 1.09 mm/N
Moving mass (Mms)	: 7.8 g
Mech. Q factor (Qms)	: 7.89
Electr. Q factor (Qes)	: 0.38
Total Q factor (Qts)	: 0.36
Equivalent volume (Vas)	: 9.8 l
DC resistance (Re)	: 5.4 Ohm
Force factor (BxL)	: 5.90 Tm
Voice coil induct. (Le)	: 0.44 mH
Voice coil diameter	: $\tilde{\sim}$ 25 mm
Voice coil former	: Kapton
Linear excursion (X <sub>MAX</sub> )	: $\pm$ 2.5 mm
Eff. cone area (Sd)	: 80 cm <sup>2</sup>
Magnet weight	: -
Magnet diameter	: $\tilde{\sim}$ 90 mm
Mounting cutout	: $\tilde{\sim}$ 120 mm
Mounting depth	: 68 mm
Mounting hole diameter	: $\tilde{\sim}$ 137 mm
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\tilde{\sim}$ 148 mm x 68 mm
Outside diameter	: $\tilde{\sim}$ 148 mm
Width	: $\tilde{\sim}$ 148 mm

---

Height	: -
Depth	: 68 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 1.25 kg
Packing unit	: 1
Type of speaker	: 5"