

## PA-4120 - PA Amplifier



### PA power amplifier

- 4 x 120 W
- Routing switches for parallel operation on 2 channels each
- Temperature-controlled fan
- Connection for external on/off switch
- LED indication for clip, protect, overtemperature and output level
- Mains operation or 24 V emergency power operation

## Tekniset tiedot:

|  |   |
|--|---|
| Peak output power                            | : -   |
| Power rating                                 | : 480 W   |
| Power rating at 2 Ohm                        | : -   |
| Power rating at 4 Ohm                        | : 4 x 120 W   |
| Power rating at 8 Ohm                        | : -   |
| Power rating at 16 Ohm                       | : -   |
| Power rating at 100 V                        | : 4 x 120 W   |
| Power rating with 4 Ohm<br>bridged operation | : -   |
| Power rating with 8 Ohm<br>bridged operation | : -   |
| Output impedance                             | : 22Â V/4Â Ohm, 50Â V/21Â Ohm, 70Â V/41Â Ohm,<br>100Â V/83Â Ohm |
| Channels                                     | : 4   |
| Zones  | : -   |
| Inputs                                       | : 1.2Â V, bal.  |
| Attenuation factor                           | : -   |
| Frequency range                              | : 55-17,000 Hz  |
| Crossover network                            | : -   |
| Crossover frequency                          | : -   |
| Integrated limiter                           | : -   |
| Equalizer bass                               | : -   |
| Equalizer midrange                           | : -   |
| Equalizer treble                             | : -   |
| S/N ratio                                    | : ? 90 dBA  |
| Crosstalk attenuation                        | : -   |
| THD  | : < 1%  |
| Mains voltage                                | : ~ 230 V   |
| Mains frequency                              | : 50 Hz   |
| Power consumption, operation                 | : 1,400 VA  |
| Power consumption, standby                   | : -   |
| Standby current                              | : -   |
| Operating voltage (possible<br>alternative)  | : DC 24 V   |
| Power supply (possible<br>alternative)       | : DC 60 A   |
| Admiss. ambient temp.                        | : 0-40 °C   |
| Width  | : 483 mm  |
| Height                                       | : 133 mm  |

Depth

: 370 mm





---

|                 |  |
|-----------------|--|
| Rack spaces, RS | : 3  |
| Weight          | : 25 kg  |
| Connections     | : 4 x XLR (inputs), screw terminals (speakers) |