

STA-200D - Amplifier



Stereo class D PA amplifier, 250 W

- 5 switchable line inputs
- Silent operation due to fanless cooling concept
- High power reserves due to generously dimensioned toroidal core transformer
- High-efficiency power amplifiers
- 3.5 mm stereo jack connection with switchable sensitivity on the front panel
- 4 x RCA input
- 2 x SPEAKER output
- 4 x terminal strip output
- 2 level controls
- Protected against short circuit, overvoltage and overtemperature
- LEDs for indicating power, overload (clip), protect and overheating
- Super slimline and robust design, 1 RS

Tekniset tiedot:

| | |
|--|---|
| Peak output power | : 300 W |
| Power rating | : 250 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : 2 x 125 W |
| Power rating at 8 Ohm | : 2 x 75 W |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : - |
| Power rating with 4 Ohm bridged operation | : - |
| Power rating with 8 Ohm bridged operation | : - |
| Output impedance | : - |
| Channels | : 2 |
| Zones | : - |
| Inputs | : 1 \hat{A} V/23 \hat{A} kOhm (RCA), 90 mV-1 V (jack) |
| Attenuation factor | : - |
| Frequency range | : 20-20,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : - |
| Equalizer midrange | : - |
| Equalizer treble | : - |
| S/N ratio | : ? 100 dBA |
| Crosstalk attenuation | : ? 56 dB |
| THD | : < 0.05% |
| Mains voltage | : \sim 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 350 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 483 mm |
| Height | : 44 mm |

Depth

: 268 mm





| | |
|-----------------|--|
| Rack spaces, RS | : 1 |
| Weight | : 5 kg |
| Connections | : 1 x 3.5 mm stereo jack 4 x RCA L/R 1 x SPEAKER L/R 1 x spring-load. speaker term. L/R |